

# ALFA MIX SERIES

THE RIGHT CHOICE IN PU PROCESS!



# THE RIGHT CHOISE IN PU PROCESS!

The Foaming Machine Alfamix Series has been designed to create a market demand ever more frequent:


- 1 Use and maintenance simple
- 2 Perfect balance between quality and price
- 3 New technologies in use
- 4 Low energy consumption

The Alfamix Series allow to produce parts with low / medium weight with open or closed mould application with the following standard specifications:

- Duly insulated tank 60 liters capacity;
- Thermoregulation via tube nest heat exchanger for heating and cooling phase;
- High efficiency axial piston pumps C-series with manual displacement;
- Axial piston mixing head with recycle;
- PLC and HMI Siemens S7-1200 series;
- Remote push button box on mixing head;



The mixing head



Control Panel

## OPTIONS

- Low revolutions stirrer on component tanks;
- Flow-meters reading on dosing pumps C-series;
- Automatic loading pumps;
- Damped flow Mixhead HPDF8 or HPDF14;



MODEL	Flow-rate Min/Max R.1:1 Gr/sec.	Flow-rate Min/Max R.2:1 Gr/sec.	Motor Power kW	Nominal Power kW	Weight Kg
ALFAMIX 30	30 - 300	45 - 225	3 - 3	13	500